



Substitute Specification
Marked-Up Copy

HYGENIC ABSORBENT ARTICLE

BACKGROUND OF THE INVENTION

[0001] 1. Field of the Invention

[0002] The present invention relates to a hygienic absorbent article for absorbing the menstrual blood and, more particularly, to a hygienic absorbent article which can be held in close contact with the wearer's body so as not to go out of position by the motion of the body.

[0003] 2. Description of Related Art

[0004] Typically, hygienic absorbent articles such as sanitary napkins are constructed to have a main body including: a liquid-impermeable back layer (back sheet); a liquid-permeable surface layer (top sheet); and an absorbent layer (absorbent core) sandwiched between the back layer and the surface layer. In addition, a pressure-sensitive adhesive layer is provided on an outer face (garment-facing face) of the back layer. By adhering the pressure-sensitive adhesive layer to an undergarment, the sanitary napkin can be prevented from going out of position with respect to the undergarment.

[0005] In order to improve close contact with the private part of a wearer, some of the sanitary napkins are provided at the center of the absorbing region with a protrusion for coming into close contact with the private part.

[0006] Conventional sanitary napkins of this type are disclosed, for example, in Japanese Unexamined Utility Model Publication No. 33721/1993 and Japanese

Unexamined Patent Publication No. 504486/1998. In both of these disclosures, a protrusion having an absorption power is fixed on the center of the liquid-receiving face of the sanitary napkin. By bringing the protrusion into close contact with the wearer's private part, the ability to trap the menstrual blood is enhanced.

[0007] In these sanitary napkins of the prior art, however, the protrusion is fixed without any degree of freedom. Therefore, ~~when~~ the outer face of the back layer is adhered to the inner face of the undergarment through the pressure-sensitive adhesive layer, but if the undergarment goes out of position from the private part to cause dislocation of the sanitary napkin, the protrusion easily leaves the private part.

[0008] ~~Especially when~~If an undergarment having a weak fastening force to the wearer's body is worn and ~~when the sanitary napkin is fixed on the undergarment by the pressure-sensitive adhesive layer, the protrusion may easily leaves detach from the crotch of a wearer together with the undergarment while the wearer is walking or in bed., thereby to~~ This deteriorates the close contact between the protrusion and the private part.

[0009] Moreover, the protrusion provided in the sanitary napkin of the prior art mainly ~~comprises~~ includes a hydrophilic fibrous layer. In a wet condition, therefore, it is difficult for the protrusion to elastically restore to its original shape. That is, when the protrusion having absorbed a liquid is pressed against the wearer's body, it easily shrinks. As a result, the protrusion cannot exhibit sufficient elastic restoring force to closely contact with the private part but easily leaves the private part, when the sanitary napkin goes out of position together with the undergarment. In addition, the protrusion thus wetted and pressed against the wearer's body easily becomes stiff, thereby giving an uncomfortable feeling to the wearer.

[0010] Moreover, since the sanitary napkin of the prior art is fixed on the undergarment through the pressure-sensitive adhesive layer provided on the back layer, it moves

together with the undergarment to cause dislocation from the private part. Therefore, it is required to interpose the absorbent layer and the back layer over a wide area between the private part and the undergarment. As a result, the entire size of the sanitary napkin becomes must be relatively large.

SUMMARY OF THE INVENTION

[0011] The present invention has been worked out in view of the foregoing shortcomings of the prior art and has an object to provide a hygienic absorbent article, a portion that ~~of which to~~ contact with the private part of a wearer is movable with respect to a main body of the article so as to keep close contact with the private part.

[0012] According to a first aspect of the invention, there is provided a hygienic absorbent article comprising: that includes the following members.

[0013] a A main body including a back layer and an absorbent layer ~~having~~ has two side edges extending in a longitudinal direction of the article and laid on the back layer.;

[0014] a A three-dimensional portion ~~extending~~ing in the longitudinal direction of the article and is provided over the absorbent layer.; ~~†~~The three-dimensional portion ~~being~~is fixed at two fixed ends thereof onto the main body.; ~~†~~The fixed ends ~~being~~is located between the two side edges of the absorbent layer.; ~~†~~The three-dimensional portion ~~including~~includes two connecting portions to rise from the fixed ends and a ~~skin-contacting~~skin-contactable portion extending between upper ends of the connecting portions to have a pair of free ends.; ~~e~~ Each free end ~~being~~is located closer to ~~corresponding~~one of the side edges of the absorbent layer than to the fixed end.; a At least an upper face of the ~~skin-contacting~~skin-contactable portion ~~being~~is made of a liquid-permeable material.; ~~and~~

[0015] ~~e~~Elastic members are provided in the three-dimensional portion to extend in the longitudinal direction of the article for applying a longitudinal elastic contractive force to the three-dimensional portion. ~~so that t~~ The three-dimensional portion is allowed to rise to have the free ends of the ~~skin-contacting~~skin-contactable portion spaced above the main body while being anchored at the fixed ends to the main body.

[0016] Here, the three-dimensional portion may be formed by folding a single sheet to extend from one fixed end and come back to the other fixed end.

[0017] According to a second aspect of the invention, ~~there is provided a~~ hygienic absorbent article comprising includes the following members.

[0018] ~~a~~A main body ~~including~~ includes a back layer and an absorbent layer having two side edges extending in a longitudinal direction of the article and laid on the back layer;

[0019] ~~f~~First and second three-dimensional portions ~~extending~~ in the longitudinal direction of the article and symmetrically are provided over the absorbent layer with respect to a longitudinally extending centerline of the absorbent layer. ~~t~~ The first and second three-dimensional portions ~~being~~ are fixed at fixed ends thereof onto the main body. ~~t~~ The fixed ends ~~being~~ are located between the two side edges of the absorbent layer. ~~e~~Each three-dimensional portion ~~includes~~ includes a connecting portion to rise from the fixed end and a ~~skin-contacting~~skin-contactable portion bent from the connecting portion outwardly to have a free end located closer to ~~e~~corresponding one of the side edges of the absorbent layer than to the fixed end. ~~a~~ At least an upper face of the ~~skin-contacting~~skin-contactable portion ~~being~~ is made of a liquid-permeable material. ~~and~~

[0020] ~~e~~Elastic members are provided in the first and second three-dimensional portions to extend in the longitudinal direction of the article for applying a longitudinal elastic contractive force to the first and second three-dimensional portion. ~~so that t~~ The first

and second three-dimensional portions are allowed to rise to have the free ends of the ~~skin-contacting~~skin-contactable portions spaced above the main body while being anchored at the fixed ends to the main body.

[0021] In the hygienic absorbent article according to the second aspect of the invention, the first three-dimensional portion may be formed from a first sheet extending over the absorbent layer from one side edge of the absorbent layer, ~~and~~ and The second three-dimensional portion may be formed from a second sheet extending over the absorbent layer from the other side edge of the absorbent layer. The connecting portion of the first three-dimensional portion and the connecting portion of the second three-dimensional portion may be joined at least partially. Preferably, the fixed end of the first three-dimensional portion and the fixed end of the second three-dimensional portion are spaced apart in a direction perpendicular to the longitudinal direction by no more than 1/2 of the distance between the two side edges of the absorbent layer. Alternatively, the first and second three-dimensional portions may be formed from a single liquid-permeable sheet to have a common fixed end.

[0022] Here, a hydrophilic material layer may further be provided inside the three-dimensional portion(s). For example, in the first aspect of the invention, a hydrophilic material layer may be provided in at least one of the connecting portion and the ~~skin-contacting~~skin-contactable portion. In the second aspect of the invention, on the other hand, a hydrophilic material layer may be provided in at least one of the connecting portion and the ~~skin-contacting~~skin-contactable portion of each three-dimensional portion, or it may be provided between the connecting portion of the first three-dimensional portion and the connecting portion of the second three-dimensional portion.

[0023] In both the first and second aspects of the invention, a pressure-sensitive adhesive layer may be provided on an outer face of the back layer for preventing dislocation of the article during use.

[0030] FIG. 3 is a sectional view taken along line III-III of FIG. 1;

[0031] FIG. 4 is a sectional view corresponding to FIG. 2 but shows a modification of the first embodiment;

[0032] FIG. 5 is a sectional view corresponding to FIG. 2 but shows a modification of the first embodiment;

[0033] FIG. 6 is a perspective view showing a second embodiment of the invention;

[0034] FIG. 7 is a sectional view taken along line VII-VII of FIG. 6;

[0035] FIG. 8 is a sectional view taken along line VIII-VIII of FIG. 6;

[0036] FIG. 9 is a sectional view corresponding to FIG. 7 but shows a modification of the second embodiment;

[0037] FIG. 10 is a sectional view corresponding to FIG. 7 but shows a modification of the second embodiment; and

[0038] FIG. 11 is a sectional view corresponding to FIG. 7 but shows a hygienic absorbent article according to a third embodiment of the invention.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0039] The present invention will be discussed hereinafter in detail in terms of the preferred embodiments according to the present invention with reference to the accompanying drawings. In the following description, numerous specific details are set forth in order to provide a thorough understanding of the present invention. It will be

obvious, however, to those skilled in the art that the present invention may be practiced without these specific details. In other instance, well-known structures are not shown in detail in order to avoid unnecessary obscurity of the present invention.

[0040] FIG. 1 is a perspective view showing a hygienic absorbent article 1, as taken from a liquid receiving side, according to a first embodiment of the invention. FIG. 2 is a sectional view taken along line II-II of FIG. 1, and FIG. 3 is a sectional view taken along line III-III of FIG. 1. Moreover, FIGS. 4 and 5 are sectional views corresponding to FIG. 2 but show modifications of the first embodiment.

[0041] The hygienic absorbent article 1, as shown in FIGS. 1 to 3, has two longitudinally extending side edges 1a and 1b, and a front edge 1c and a rear edge 1d. A liquid-impermeable back layer 2, for to confronting an external wear such as an undergarment, is sized equally to the entirety of is provided as a back portion of the hygienic absorbent article 1. ~~Over the back layer 2, there is laid a~~ An absorbent layer 3 is laid over the back layer 2. This absorbent layer 3 has two longitudinally extending side edges 3a and 3b, and a front edge 3c and a rear edge 3d, but is sized just smaller than the back layer 2. In the hygienic absorbent article 1, the area having the absorbent layer 3 is called a liquid absorbing region 4.

[0042] As shown in a transverse section of FIG. 2, side flaps 5 and 5 are respectively formed between the side edges 3a and the side edge 1a and between the side edges 3b and the side edge 1b, ~~there are formed side flaps 5 and 5, respectively. On the other hand,~~ Rear flaps 6 and 6 are respectively formed between the front edge 3c and the front edge 1c and between the rear edge 3d and the rear edge 1d, there are formed front and rear flaps 6 and 6, respectively.

[0043] The hygienic absorbent article 1 is provided on its liquid receiving side with a liquid-permeable sheet 8. A three-dimensional portion 10 is formed ~~Over~~ the liquid absorbing region 4 having the absorbent layer 3, as shown in FIG. 1, ~~there is provided~~

a The three-dimensional portion 10 is formed from the liquid-permeable sheet 8 and extendsing over a region indicated by a longitudinal length L. In the region L, as shown in FIG. 2, the three-dimensional portion 10 is formed from a portion of the liquid-permeable sheet 8 extending between 11a and 11b.,~~wherein~~ The numeral 11a indicates a first fixed end of the three-dimensional portion 10 which is spaced toward the center of the absorbent layer 3 from the side edge 3a by a predetermined distance.~~;~~ ~~and~~ The numeral 11b indicates a second fixed end of the three-dimensional portion 10 which is spaced toward the center of the absorbent layer 3 from the side edge 3b by a predetermined distance.

[0044] The first fixed end 11a and the second fixed end 11b are arranged ~~at symmetric positions~~symmetrically with respect to a centerline O-O extending longitudinally of the hygienic absorbent article 1. The first fixed end 11a and the second fixed end 11b are formed such that the liquid-permeable sheet 8 and the upper face of the absorbent layer 3 are fixed together (e.g., bonded with a hot-melt adhesive or thermally fused) on a continuous line or an intermittent line parallel to the centerline O-O.

[0045] As shown in FIG. 2, the liquid-permeable sheet 8 also provides a surface layer 8a. The layer 8a covers~~covering~~ the surface of the absorbent layer 3 at its portion extending from the side edge 3a of the absorbent layer 3 to the first fixed end 11a and at its portion extending from the side edge 3b of the absorbent layer 3 to the second fixed end 11b. Moreover, the liquid-permeable sheet 8 has extensions 8b and 8b extending beyond the side edges 3a and 3b of the absorbent layer 3, respectively. Here, the back layer 2 also has extensions 2a and 2a extending beyond the side edges 3a and 3b of the absorbent layer 3, respectively. At the side flaps 5 and 5, the extensions 2a and 2a of the back layer 2 and the extensions 8b and 8b of the liquid-permeable sheet 8 are bonded with a hot-melt type adhesive or the like.

[0046] At the front and rear flaps 6 and 6, ~~to~~extensions of the back layer 2 extending extends beyond the front edge 3c and the rear edge 3d of the absorbent layer 3 and

face of the back layer 2.

[0050] In the three-dimensional portion 10 and the folded portion 8c, as shown in FIGS. 2 and 3, there are provided a plurality of elastic members 13 in the form of filaments or strips. These elastic members 13 are disposed between and fixed to the confronting faces of the folded liquid-permeable sheet 8. In the three-dimensional portion 10 shown in FIG. 2, the elastic members 13 are disposed at least in the ~~skin-contacting~~skin-contactable portion 12e to extend in parallel with the free ends 12c and 12d of the ~~skin-contacting~~skin-contactable portion 12e.

[0051] The elastic members 13 are fixed to the liquid-permeable sheet 8 while being stretched to a predetermined length. Therefore, in a free state where no external force is applied to the hygienic absorbent article 1, the three-dimensional portion 10 is elastically contracted by elastic contractive force of the elastic members 13 in such a direction that the front end 10c and the rear end 10d ~~may approach each other~~. As a result, the hygienic absorbent article 1 is so curved and deformed that the back layer 2 may bulge outward. As a result of this curved/deformed state, the free ends 12c and 12d of the ~~skin-contacting~~skin-contactable portion 12e of the three-dimensional portion 10 ~~leave~~rise above the surface layer 8a ~~so that the three-dimensional portion 10 rises~~ into a T-shaped state in the region L.

[0052] The hygienic absorbent article 1 may further be provided on the outer face (or the lower face in the drawings) of the back layer 2 with a pressure-sensitive adhesive layer (not shown). With this pressure-sensitive adhesive layer, the hygienic absorbent article 1 can be fixed on the inner face of the external wear such as an undergarment, like conventional sanitary napkins. By fixing the back layer 2 on the inner face of the undergarment through the pressure-sensitive adhesive layer and by putting this undergarment on a wearer's body, the liquid-receiving side of the hygienic absorbent article 1 can be applied to the private part of the wearer.

[0053] In the worn state, the ~~skin-contacting~~skin-contactable portion 12e of the three-dimensional portion 10 comes into close contact with the wearer's private part, ~~and then,~~ ~~the~~ The absorbent layer 3 is pushed onto the wearer's body by the undergarment, so that the connecting portions 12a and 12b are flexed to bring the ~~skin-contacting~~skin-contactable portion 12e into substantial contact with the surface layer 8a. Here, since the ~~skin-contacting~~skin-contactable portion 12e of the three-dimensional portion 10 is always biased away from the surface layer 8a by the elastic force of the elastic members 13, the ~~skin-contacting~~skin-contactable portion 12e can be always kept in close contact with the wearer's private part.

[0054] Therefore, even if an undergarment having a poor fastening force is worn and the back layer 2 fixed on the undergarment through the pressure-sensitive adhesive layer ~~laterally goes out of position together~~shifts with the undergarment, the skin-~~contacting~~skin-contactable portion 12e is ~~always enabled to keep abutment~~will still remain abutted against the private part by free deformation of the connecting portions 12a and 12b.

[0055] Accordingly, a menstrual blood discharged from the wearer's private part can always be received by the ~~skin-contacting~~skin-contactable portion 12e of the three-dimensional portion 10. In the case where no displacement of the undergarment occurs, the menstrual blood thus received permeates through the ~~skin-contacting~~skin-contactable portion 12e and further through the surface layer 8a and is then absorbed by the absorbent layer 3. In the case where the back layer 2 ~~moves laterally together~~shifts with the undergarment as described above so that the absorbent layer 3 goes laterally out of position, ~~on the other hand~~, the menstrual blood permeates through the ~~skin-contacting~~skin-contactable portion 12e, through the connecting portions 12a and 12b, and further through the surface layer 8a and can reach the absorbent layer 3. Therefore, the menstrual blood hardly leaks laterally ~~off~~from the hygienic absorbent article 1.

[0056] Here, after absorption of the menstrual blood, the absorbent layer 3 becomes

layer 15.

[0059] In the modification shown in FIG. 5, over the back layer 2, there is placed the absorbent layer 3, over which a liquid-permeable sheet 17 is laid. This liquid-permeable sheet 17 provides a surface layer 17a covering the absorbent layer 3 at its portion extending between the two side edges 3a and 3b of the absorbent layer 3. Moreover, the liquid-permeable sheet 17 has extensions 17b and 17b extending outwardly beyond the two side edges 3a and 3b, respectively. At the side flaps 5 and 5, the extensions 2a and 2a of the back layer 2 and the extensions 17b and 17b are fixed with a hot-melt type adhesive or the like. Moreover, a liquid-permeable sheet 18 forming a three-dimensional portion 10B is disposed over the surface layer 17a. The liquid-permeable sheet 18 forming the three-dimensional portion 10B has the connecting portions 12a and 12b, which rise from the first fixed end 11a and the second fixed end 11b fixed to the liquid-permeable sheet 17 forming the surface layer 17a. These connecting portions 12a and 12b are joined together at their upper ends to form a join portion 12f. The skin-contactable portion 12e is formed ~~Over this join portion 12f, moreover, there is formed the band shaped, skin-contacting~~ The skin-contactable portion 12e which has the free ends 12c and 12d on the two sides. Here, it is, of course, possible to provide the hydrophilic material layer 15 of FIG. 4 in the skin-contactingskin-contactable portion 12e of FIG. 5, and to provide the elastic members 14 of FIG. 4 between the connecting portions 12a and 12b of FIG. 5.

[0060] Although not shown in drawings, ~~moreover,~~ it is also possible to provide a hydrophilic material layer similar to the hydrophilic material layer 15 between the connecting portions 12a and 12b forming the stem of the three-dimensional portions 10, 10A and 10B. With the hydrophilic material layer provided between the connecting portions 12a and 12b, the stem of the three-dimensional portion is allowed to absorb a small amount of menstrual blood. Therefore, the menstrual blood is effectively prevented from leaking laterally of the hygienic absorbent article 1. ~~Here, if the~~ A hydrophilic material layer that is thinner and softer than the absorbent layer 3 can be

layer 21a at its portion covering the absorbent layer 3 from the side edge 3a of the absorbent layer 3 to the first fixed end 31a; and (b) an extension 21b at its portion extending outward beyond the side edge 3a of the absorbent layer 3. The extension 2a of the back layer 2, extending outward beyond the side edge 3a, and the extension 21b are bonded with a hot-melt type adhesive or the like to form ~~one~~ a side flap 5. Similarly, the second liquid-permeable sheet 22 thus folded in two provides: (a) a surface layer 22a at its portion covering the absorbent layer 3 from the side edge 3b of the absorbent layer 3 to the second fixed end 31b; and (b) an extension 22b at its portion extending outward beyond the side edge 3b of the absorbent layer 3. The extension 2a of the back layer 2, extending outward beyond the side edge 3b, and the extension 22b are bonded with a hot-melt type adhesive or the like to form the other side flap 5. At the front and rear flaps 6 and 6 shown in FIG. 6, ~~moreover,~~ the first liquid-permeable sheet 21 and the second liquid-permeable sheet 22 are bonded to the back layer 2.

[0065] ~~Moreover,~~ The first liquid-permeable sheet 21 provides a first three-dimensional portion 30A at a portion rising from the first fixed end 31a; ~~and~~ The second liquid-permeable sheet 22 provides a second three-dimensional portion 30B at a portion rising from the second fixed end 31b. These first three-dimensional portion 30A and second three-dimensional portion 30B are made symmetric with respect to the centerline O-O to have connecting portions (rising walls) 32a and 32b rising from the first fixed end 31a and the second fixed end 31b, respectively, and ~~skin-contacting~~ skin-contactable portions 34a and 34b bent to the left and right from the upper ends of the connecting portions 32a and 32b, respectively. The connecting portions 32a and 32b are bonded to each other. The ~~skin-contacting~~ skin-contactable portion 34a has a free end 33a located closer to the side edge 3a than the first fixed end 31a; ~~and~~ The ~~skin-contacting~~ skin-contactable portion 34b has a free end 33b located closer to the side edge 3b than the second fixed end 31b.

[0066] As shown in FIG. 6, the first and second three-dimensional portions 30A and 30B have front and rear ends 30c and 30d. At the front and rear end portions (as

located outside of the front and rear ends 30c and 30d) of the hygienic absorbent article 1A, as shown in FIG. 8, the first liquid-permeable sheet 21 and the second liquid-permeable sheet 22 provide flat, folded portions 21c and 22c, respectively. These folded portions 21c and 22c are folded back in opposite directions with respect to the centerline O-O, and are fixed as a whole onto the absorbent layer 3 or the back layer 2 with an adhesive.

[0067] The first liquid-permeable sheet 21 and the second liquid-permeable sheet 22 are provided with a plurality of elastic members 35 extending longitudinally of the article 1A. Therefore, the front ends 30c and the rear ends 30d of the first three-dimensional portion 30A and the second three-dimensional portion 30B are pulled to each other by the elastic contractive force of the elastic members 35 to curve the hygienic absorbent article 1A. As a result, the first three-dimensional portion 30A and the second three-dimensional portion 30B are raised into a T-shaped state away from the surface layers 21a and 22a.

[0068] As in the first embodiment, a pressure-sensitive adhesive layer (not shown) may also be provided on the back layer 2 of the hygienic absorbent article 1A. When the hygienic absorbent article 1A is worn by fixing the pressure-sensitive adhesive layer of the back layer 2 on an undergarment, the first three-dimensional portion 30A and the second three-dimensional portion 30B according to the second embodiment function substantially like the three-dimensional portions 10, 10A and 10B shown in the sections of FIGS. 2, 4 and 5. As a result, the ~~skin-contacting~~skin-contactable portions 34a and 34b can contact closely with the wearer's private part so that their close contact with the private part can be easily kept maintained even if the back layer 2 moves.

[0069] The ~~skin-contacting~~skin-contactable portions 34a and 34b are formed from the liquid-permeable sheets 21 and 22, so that the menstrual blood given to the ~~skin-contacting~~skin-contactable portions 34a and 34b permeates into the ~~skin-contacting~~skin-contactable portions 34a and 34b and through the connecting portions 32a and 32b and

is absorbed by the absorbent layer 3.

[0070] FIG. 9 shows one modification of the second embodiment. In this modification, another liquid-permeable sheet 23 is laid on the absorbent layer 3. This liquid-permeable sheet 23 provides: (a) a surface layer 23a at its portion covering the absorbent layer 3; and (b) extensions 23b and 23b at its portions extending outward beyond the side edges 3a and 3b of the absorbent layer 3. At the side flaps 5 and 5, the extensions 2a and 2a of the back layer 2 and the extensions 23b and 23b are bonded with a hot-melt type adhesive or the like. On the liquid-permeable sheet 23, there are laid the first liquid-permeable sheet 21 and the second liquid-permeable sheet 22 individually in a two-folded state. The first liquid-permeable sheet 21 extends from the side edge 1a of the hygienic absorbent article 1A to over the surface layer 23a thereby to form a first three-dimensional portion 30C rising from the fixed end 31a, at the central portion. On the other hand, the second liquid-permeable sheet 22 extends from the side edge 1b of the hygienic absorbent article 1A to over the surface layer 23a thereby to form a second three-dimensional portion 30D rising from the fixed end 31b, at the central portion. The first three-dimensional portion 30C has ~~the~~ a connecting portion 32a and ~~the skin-contacting~~ a skin-contactable portion 34a, and the second three-dimensional portion 30D has ~~the~~ a connecting portion 32b and ~~the skin-contacting~~ a skin-contactable portion 34b. The individual three-dimensional portions 30C and 30D are provided with elastic members 36 extending longitudinally of the article 1A. As shown in FIG. 9, the first fixed end 31a and the second fixed end 31b are formed at symmetric positions with respect to the centerline O-O while being spaced by a distance W2.

[0071] FIG. 10 shows another modification of the second embodiment. In the modification shown in FIG. 10, the liquid-permeable sheet 23 is laid on the absorbent layer 3 to form ~~the~~ a surface layer 23a covering the absorbent layer 3, as in the modification shown in FIG. 9. Over this surface layer 23a, a first three-dimensional portion 30E is formed from ~~the~~ a first liquid-permeable sheet 21, and a second three-

restoring force when compressed (vertically crushed) by the abutting pressure against the skin. Therefore, the three-dimensional portions 30E and 30F of FIG. 10 can further improve the ~~close contact between the skin-contacting~~skin-contactable portions 34a and 34b and the private part.

[0074] FIG. 11 is a sectional view showing a third embodiment having a shape similar to that of the second embodiment of the invention. Here, the detailed description of the portions having the same constructions as those of the first and second embodiments will be omitted. The common members will be designated ~~by designating them by the~~ common reference numerals.

[0075] In the third embodiment shown in FIG. 11, on the back layer 2 having the pressure-sensitive adhesive layer (not shown) on its outer face, there is laid the absorbent layer 3, on which there is laid the liquid-permeable sheet 23. The liquid-permeable sheet 23 provides the surface layer 23a at its portion covering the surface of the absorbent layer 3. Over the liquid-permeable sheet 23, moreover, there is provided a liquid-permeable sheet 41 folded in two.

[0076] This liquid-permeable sheet 41 is of a band shaped and extends longitudinally of in the article. At least in a region L1 of FIG. 6, the longitudinally extending center portion of the band-shaped liquid-permeable sheet 41 is intermittently or continuously fixed (e.g., bonded with an adhesive or thermally fused) on the surface of the liquid-permeable sheet 23 forming the surface layer 23a, ~~thereby forming to form~~ a fixed end 42. A first three-dimensional portion 30G and a second three-dimensional portion 30H are formed symmetrically with respect to the fixed end 42. The first three-dimensional portion 30G has a connecting portion (rising wall) 43a and a ~~skin-contacting~~skin-contactable portion 44a; ~~and~~ The second three-dimensional portion 30H has a connecting portion (rising wall) 43b and a ~~skin-contacting~~skin-contactable portion 44b. In the liquid-permeable sheet 41, ~~moreover, there are fixed~~ a plurality of elastic members 46 are fixed and extending longitudinally ~~in~~ of the article. At the front and rear

[0079] On the other hand, a length of the three-dimensional portions, which is indicated at L in FIG. 1 and at L1 in FIG. 6, is preferably within a range of 150 to 400 mm, more preferably within a range of 200 to 360 mm. By setting the length L or L1 within the specified ranges to be sufficiently long in the longitudinal direction of the article, the ~~skin-contacting~~skin-contactable portion can contact closely with not only the vicinities of the labia of the private part but also the clearance between the buttocks, so that the menstrual blood can be suppressed from leaking toward the buttocks while the wearer is in bed.

[0080] Moreover, the height of the three-dimensional portions rising from the fixed ends is within a range of 5 to 50 mm, preferably within a range of 10 to 40 mm, or more preferably within a range of 10 to 25 mm.

[0081] As has been described hereinabove, the hygienic absorbent articles of the foregoing embodiments and modifications thereof can be used by simply applying the ~~skin-contacting~~skin-contactable portion(s) to the wearer's private part. However, they may also be used by fitting the ~~skin-contacting~~skin-contactable portion(s) between the labia of a female genital organ. In detail, the ~~skin-contacting~~skin-contactable portion of the three-dimensional portion (10, 10A, or 10B) or the ~~skin-contacting~~skin-contactable portions of the first and second three-dimensional portions (30A and 30B, 30C and 30D, 30E and 30F, or 30G and 30H) may be fitted between the labia so as to be retained by the female genital organ with use of closing force of the labia. As a result, the hygienic absorbent article can be comfortably worn as a whole as if it were integral with the female genital organ. In this case, it is preferable not to provide any pressure-sensitive adhesive layer on the outer face of the back layer 2 so that the back layer 2 may not be fixed on the inner face of the undergarment. The hygienic absorbent article thus worn hardly ~~goes-shifts~~out of position from the female genital organ even if the undergarment ~~itself goes-out-of-position-moves~~itself goes-out-of-position-moves with respect to the crotch of a wearer. When a menstrual blood is discharged from the female genital organ, therefore, it is always received by the ~~skin-contacting~~skin-contactable portion. Then, the menstrual

blood permeates through the skin-contacting~~skin-contactable~~ portion, flows down the connecting portion, and thereafter, is absorbed by the absorbent layer 3. In the case where the hydrophilic material layer 15 is provided in the skin-contacting~~skin-contactable~~ portion, as shown in FIG. 4, a small amount of menstrual blood discharged from the organ can be absorbed mainly by this hydrophilic material layer 15. When a large amount of menstrual blood is discharged, ~~on the other hand,~~ most of the menstrual blood not absorbed by the hydrophilic material layer 15 can be absorbed by the underlying absorbent layer 3.

[0082] In the case where the hygienic absorbent article should be is retained by the labia, it is preferred that the hygienic absorbent article has the symmetrical first and second three-dimensional portions in which the ~~skin-contacting~~skin-contactable portions can behave relatively independently of each other, as shown in FIGS. 7, 9, 10 and 11. Especially when the first and second three-dimensional portions are slightly spaced apart from each other so as to enable the ~~skin-contacting~~skin-contactable portions to behave independently of each other, as shown in FIGS. 9, 10 and 11, the ~~skin-~~skin-~~contacting~~skin-contactable portions can be easily retained between the labia.

[0083] In the embodiments and modifications shown in FIGS. 7, 9, 10 and 11, ~~there may be adopted~~ a structure in which a hydrophilic material layer similar to the hydrophilic material layer 15 of FIG. 4 may be adopted ~~is provided~~ in the skin-~~contacting~~skin-contactable portion of each three-dimensional portion. With the hydrophilic material layer being provided in the ~~skin-contacting~~skin-contactable portion, this ~~skin-contacting~~skin-contactable portion can be thickened to have a certain degree of stiffness. Therefore, when retained between the labia, the paired ~~skin-contacting~~skin-contactable portions do not easily come off the labia. Moreover, such a thin, hydrophilic material layer similar to the hydrophilic material layer 15 of FIG. 4 may be provided between the connecting portions 32a and 32b of FIG. 7. It may also be provided in each of the connecting portions 32a and 32b of FIGS. 7, 9, and 10 or in each of the connecting portions 43a and 43b of FIG. 11 (i.e., between the confronting

inorganic filler partially or wholly to make it porous.

[0088] In the case where the pressure-sensitive adhesive layer to be retained on an external wear such as an undergarment is provided on the outer face of the back layer 2, the pressure-sensitive adhesive layer is preferably elongated in the longitudinal direction of the hygienic absorbent article. In this case, moreover, it is preferable that the pressure-sensitive adhesive layer is covered with a release paper for protecting it before use.

[0089] The absorbent layer 3 may be formed from fluff pulp, a laminate of tissue paper, air-laid pulp, an air-laid nonwoven fabric containing fusible fibers, a foamed sheet treated to be hydrophilic, a foamed sheet of cellulose, or a sheet containing superabsorbent polymer. The material for the superabsorbent polymer is exemplified by a granular or fibrous substance selected from a polymer composed mainly of acrylic acid, a graft polymer of starch/acrylic acid, starch, and carboxymethylcellulose.

[0090] The absorbent layer 3 is preferred to have a measured value within a range of 5 to 70 mm according to a bending resistance measuring test using the 45-degree cantilever method based on JIS L 1096. Within this range, the absorbent layer 3 can be prevented from being torsionally deformed, and no excessive stiffness is given to the wearer. Here, the confinement of the bending resistance within that range may be supplemented by applying a mechanical pressure to the absorbent layer to have a pressed groove.

[0091] Moreover, the absorbent layer 3 is preferred to have a thickness of 1.0 to 5.0 mm.

[0092] The liquid-permeable sheet 17 for forming the surface layer 17a shown in FIG. 5 or the liquid-permeable sheet 23 for forming the surface layer 23a shown in FIGS. 9 to 11 may be formed from an absorbent material having a wet strength such as air-laid

pulp, an apertured plastic film as a liquid-permeable material, a nonwoven fabric composed of hydrophobic synthetic fibers which are treated to be hydrophilic, or an apertured nonwoven fabric.

[0093] On the other hand, the liquid-permeable sheet (or the liquid-permeable material) for forming the three-dimensional portions 10, 10A, 10B, 30A and 30B, 30C and 30D, 30E and 30F, and 30G and 30H of the foregoing individual embodiments may be a through air nonwoven fabric having a high bulk and a low liquid residue, or an apertured plastic film having a high liquid shielding effect. For example, the through air nonwoven fabric is made of bicomponent fibers having sheath/core structure, and is preferred to have a basis weight within a range of 20 to 40 g/m.² and a thickness within a range of 0.3 to 1.5 mm. On the other hand, the apertured plastic film is preferably made of an olefin resin having a density within a range of 0.90.times.10.⁶ to 0.93.times.10.⁶ g/cm.³ to have a basis weight within a range of 20 to 35 g/m.². At this time, the surface of the apertured plastic film is preferred to have an open area ratio within a range of 30 to 70%. Here, each aperture may be of a round, rhomboid or polygonal shape but should not be limited thereto. Moreover, the area of each aperture or the arrangement pattern of the apertures should not be especially limited. Alternatively, the liquid-permeable sheet (or the liquid-permeable material) for forming the three-dimensional portions may be a point-bonded nonwoven fabric, a spun-laced nonwoven fabric or an air-laid nonwoven fabric. These nonwoven fabrics may contain regenerated cellulose fibers (such as viscose rayon or acetate rayon) or natural cellulose fibers, in addition to the aforementioned bicomponent fibers. A spun-bonded or melt-blown nonwoven fabric may also be employed. The apertured plastic film or the nonwoven fabric may be employed alone or laid on another apertured plastic film or nonwoven fabric having the same structure. Of course, it is possible to laminate different kinds of apertured plastic film or nonwoven fabric.

[0094] In the foregoing embodiments and their modifications, each three-dimensional

• •

Disclosed is a hygienic absorbent article including: a back layer; an absorbent layer; and a three-dimensional portion. The three-dimensional portion ~~to rises~~ in a T-shaped state over the absorbent layer ~~due to~~ because of the longitudinal elastic contractive force of elastic members ~~provided in~~ disposed within the three-dimensional portion. The three-dimensional portion has: connecting portions fixed onto the absorbent layer; and a ~~skin-contacting~~ contactable portion connected to the absorbent layer through the connecting portions and having a pair of free ends.